

## TECHNICAL SHEETS : SEMI-AUTONOMOUS - MIG

### MIGMATIC 171 / 271 MODEL



#### DETAILS AND WEIGHTS \*

MIGMATIC 171	
POWER RANGE	15 - 30 A.
NOMINAL POWER	150 A. at 35%
WEIGHT (kg)	633
SUPPLY	230 V. / 50 Hz / Singlephase
SPEED TREAD	1,8 to 18 t/min

MIGMATIC 271	
POWER RANGE	15 - 32 A.
NOMINAL POWER	240 A. at 20%
WEIGHT (kg)	85
SUPPLY	230 V. / 50 Hz / Singlephase
SPEED TREAD	1,8 to 18 t/min

#### OPTIONAL EQUIPMENT

- MIG torches
- Shielded liter low

## TECHNICAL SHEETS : SEMI-AUTONOMOUS - MIG

### MIGMATIC 273 / 333 / 383 MODEL



#### DETAILS AND WEIGHTS \*

MIGMATIC 273	
POWER RANGE	15 - 32 A.
NOMINAL POWER	190 A. at 60%
WEIGHT (kg)	88
SUPPLY	400 V. / 50 Hz / Threephase (230 V. Threephase on demand)
SPEED TREAD	1,8 to 18 t/min

MIGMATIC 333	
POWER RANGE	15 - 32 A.
NOMINAL POWER	240 A. at 20%
WEIGHT (kg)	99
SUPPLY	400 V. / 50 Hz / Threephase (230 V. Threephase on demand)
SPEED TREAD	1,8 to 18 t/min
ENTRAINEMENT	2 shingles, 20 positions

MIGMATIC 383	
POWER RANGE	15 - 36 A.
NOMINAL POWER	310 A. at 20%
WEIGHT (kg)	108
SUPPLY	400 V. / 50 Hz / Threephase (230 V. Threephase on demand)
SPEED TREAD	1,8 to 18 t/min
ENTRAINEMENT	4 shingles, 30 positions

#### OPTIONAL EQUIPMENT

- MIG torches
- Shielded liter low
- Polarity inverters
- A/V digital kit

## TECHNICAL SHEETS : SEMI-AUTONOMOUS - MIG

### BLU-PAK 35 / 45 MODEL



#### DETAILS AND WEIGHTS \*

BLU-PAK 35	
POWER RANGE	16 - 38 A.
NOMINAL POWER	300 A. / 29 V. to 60%
WEIGHT (kg)	146
SUPPLY	400 V. / 50 Hz / Threephase (230 V. Threephase on demand)
DÉVIDOIRS	ST44 compatible with Ø 0,6 to 1,6 mm

BLU-PAK 45	
POWER RANGE	14 - 47 A.
NOMINAL POWER	400 A. / 34 V. to 60%
WEIGHT (kg)	158
SUPPLY	400 V. / 50 Hz / Threephase (230 V. Threephase on demand)
DÉVIDOIRS	ST44 compatible with Ø 0,6 to 1,6 mm

#### OPTIONAL EQUIPMENT

- Reel connecting beams 3, 5 and 10 m.
- Version with torches cooler
- MIG torches

## TECHNICAL SHEETS : SEMI-AUTONOMOUS - MIG

### DELTAWED 403 / 602 / 852 MODEL



#### DETAILS AND WEIGHTS \*

DELTAWED 403	
POWER RANGE	10 - 32 A.
NOMINAL POWER	300 A. at 100%
WEIGHT (kg)	147
SUPPLY	230/400 V. / 50 Hz / Threephase
EQUIPMENT	Digital display, detachable fan, 2 inductances

DELTAWED 602	
POWER RANGE	10 - 38 A.
NOMINAL POWER	450 A. at 100%
WEIGHT (kg)	174
SUPPLY	230/400 V. / 50 Hz / Threephase
SPEED TREAD	1,8 à 18 t/min
EQUIPMENT	Digital display, detachable fan, 2 inductances

DELTAWED 852	
POWER RANGE	10 - 44 A.
NOMINAL POWER	650 A. at 100%
WEIGHT (kg)	214
SUPPLY	230/400 V. / 50 Hz / Threephase
EQUIPMENT	Digital display, detachable fan, 2 inductances

#### OPTIONAL EQUIPMENT

- MIG torches
- Shielded liter low
- Polarity inverters
- A/V digital kit