

TECHNICAL SHEETS : SEMI-AUTONOMOUS - TIG

MAXSTAR 150 STH MODEL



DETAILS AND WEIGHTS *

MAXSTAR 150 STH	
POWER RANGE	1 - 160 A.
NOMINAL POWER	150 A. à 30%
WEIGHT (kg)	6.2
ALIMENTATION	230 V. / 50 Hz / Singlephase
POWER TYPE	Continuous

OPTIONAL EQUIPMENT

- Torches TIG
- Protection case
- Mass and electrode holder
- Litter flow

MAXSTAR 200 DX MODEL



DETAILS AND WEIGHTS *

MAXSTAR 200 DX	
POWER RANGE	1 - 200 A.
NOMINAL POWER	200 A. / 28 V. à 40%
WEIGHTS (kg)	15
ALIMENTATION	230/400 V. / 50 Hz / Monophasée ou Triphasée, 200 à 500 V.
POWER TYPE	Continu

OPTIONAL EQUIPMENT

- Torches TIG
- Control

TECHNICAL SHEETS : SEMI-AUTONOMOUS - TIG

MAXSTAR 350/700 MODEL



DETAILS AND WEIGHTS *

MAXSTAR 350	
POWER RANGE	5 - 350 A.
NOMINAL POWER	300 A. / 32 V. à 60%
WEIGHTS (kg)	61
ALIMENTATION	Autoline 380-575 V. / 50 Hz / Threephase
MEMORY	9 programmes
POWER TYPE	Continuous

MAXSTAR 700	
POWER RANGE	5 - 700 A.
NOMINAL POWER	600 A. / 32 V. à 61%
WEIGHTS (kg)	90
ALIMENTATION	230 V. / 50 Hz / Singlephase or Threephase
POWER TYPE	Continuous

OPTIONAL EQUIPMENT

- Torches TIG
- Trolley
- Control
- Cooler

TECHNICAL SHEETS : SEMI-AUTONOMOUS - TIG

DYNASTY 200 DX MODEL



DETAILS AND WEIGHTS *

DYNASTY 200 DX	
POWER RANGE	1 - 200 A.
NOMINAL POWER	200 A. à 20%
WEIGHTS (kg)	21
ALIMENTATION	230/400 V. / 50 Hz / Singlephase or Threephase from 120 to 460 V.
POWER TYPE	Alternatif

OPTIONAL EQUIPMENT

- Torches TIG
- Control

DYNASTY 350/700 MODEL



DETAILS AND WEIGHTS *

DYNASTY 350	
POWER RANGE	5 - 350 A.
NOMINAL POWER	300 A. / 32 V. à 60%
WEIGHTS (kg)	61
ALIMENTATION	380/575 V. / 50 Hz / Triphasée
POWER TYPE	Alternatif

DYNASTY 700	
POWER RANGE	5 - 750 A.
NOMINAL POWER	600 A. / 32 V. à 60%
WEIGHTS (kg)	90
ALIMENTATION	380/575 V. / 50 Hz / Triphasée
POWER TYPE	Alternatif

OPTIONAL EQUIPMENT

- Torches TIG
- Trolley
- Control
- Cooler

TECHNICAL SHEETS : SEMI-AUTONOMOUS - TIG

SYNCROWAVE 250 DX/350 LX MODEL



DETAILS AND WEIGHTS *

SYNCROWAVE 250 DX	
POWER RANGE	5 - 310 A.
NOMINAL POWER	250 A. / 30 V. à 40%
WEIGHTS (kg)	176
ALIMENTATION	230/400 V. / 50 Hz / Singlephase
COURANT	Continuous

SYNCROWAVE 350 LX	
POWER RANGE	3 - 400 A.
NOMINAL POWER	350 A. / 34 V. à 40%
WEIGHTS (kg)	234
ALIMENTATION	230/400 V. / 50 Hz / Singlephase
POWER TYPE	Continuous

OPTIONAL EQUIPMENT

- Torches TIG
- Trolley
- Control
- Cooler