

## TECHNICAL SHEETS : PROFESSIONAL HULS

### LANDING CRAFT SERIAL : 21' - 26'



#### COMPOSITION

- Deep "V" hull
- Marine alloy 5086 and 5052 aluminum
- Double welding, entire hull
- Self-draining and non-slip deck
- Aluminum tank below deck
- High resistance cleat
- 12 V. DC electrical system
- Hydraulic steering
- ABYC manufacturing standard
- Zinc anode(s)
- Accessoires and modifications on request

ZONE	THICKNESS	ALUMINIUM
HULL	0.250"	#5086
SIDE	0.190"	#5086
STERN	0.250"	#5086
DECK	0.190"	#5052
STORAGE BOX	0.190"	#5052
CABIN	0.190"	#5052

#### DIMENSIONS AND WEIGHT \*

	V-BARGE					
	21'	22'	23'	24'	25'	26'
LENGTH	21'	22'	23'	24'	25'	26'
WIDTH	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"
HEIGHT IN MIDDLE	43"	43"	43"	43"	43"	43"
FRANC BORD	36"	36"	36"	36"	36"	36"
DRAUGHT	15"	15"	15"	15"	15"	15"
ANGLE KEEL	15°	15°	15°	15°	15°	15°
TANK (gal)	60	60	100	100	100	100
SOQUET - 10'	6	6	6	6	6	6
LOADING CAPACITY (lbs)	3100	3300	3500	3700	3900	4100
MAXIMUM HP	150	150	200	250	300	300
MOTOR	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin

\* : dimensions and weights are not contractual