

## TECHNICAL SHEETS : PROFESSIONAL HULS

### LAW ENFORCEMENT SERIAL : 21' - 34'



#### COMPOSITION

- Deep "V" hull
- Marine alloy 5086 and 5052 aluminum
- Double welding, entire hull
- Self-draining and non-slip deck
- Aluminum tank below deck
- High resistance cleat
- 12 V. DC electrical system
- Hydraulic steering
- ABYC manufacturing standard
- Zinc anode(s)
- Air/Foam protection system
- Anti-shock seat
- Accessoires and modifications on request
- Propulsion : Hors Bord, Tri Bord, Diesel, Gas

ZONE	THICKNESS	ALUMINIUM
HULL	0.250"	#5086
SIDE	0.190"	#5086
STERN	0.250"	#5086
DECK	0.190"	#5052
STORAGE BOX	0.190"	#5052
CABIN	0.190"	#5052

#### DIMENSIONS AND WEIGHT \*

LAW ENFORCEMENT								
LENGTH	21'	23'	25'	27'	28'	30'	32'	34'
WIDTH	8' 6"	8' 6"	8' 6"	8' 6"	10'	10'	10'	10'
DRAUGHT	18"	18"	22"	22"	22"	22"	22"	22"
ANGLE KEEL	18°	18°	18°	18°	21°	21°	21°	21°
TANK (gal)	100	100	150	150	200	300	300	300
SOQUET - 10'	6	6	6	6	8	8	8	8
OUTBOARD	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
INBOARD	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
HP MINIMUM	200	225	225	300	400	450	475	500
HP MAXIMUM	250	350	450	500	600	700	900	1050

\* : dimensions and weights are not contractual