

TECHNICAL SHEETS : PROFESSIONAL HULS

S SERIAL : 22' - 28'



COMPOSITION

- Deep "V" hull
- Marine alloy 5086 and 5052 aluminum
- Double welding, entire hull
- Self-draining and non-slip deck
- Aluminum tank below deck
- 12 V. DC electrical system
- Hydraulic steering
- Sensor plate
- Zinc anode(s)
- Aluminium console feature a reinforced bumper breeze
- Accessoires and modifications on request

ZONE	THICKNESS	ALUMINIUM
HULL	0.250"	#5086
SIDE	0.190"	#5086
STERN	0.250"	#5086
DECK	0.190"	#5052
STORAGE BOX	0.190"	#5052
CABIN	0.190"	#5052

DIMENSIONS AND WEIGHT *

S SERIE							
LENGTH	22'	23'	24'	25'	26'	27'	28'
WIDTH	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"
HEIGHT IN MIDDLE	53"	53"	53"	53"	53"	53"	53"
DRAUGHT	18"	18"	22"	22"	22"	22"	22"
ANGLE KEEL	18°	18°	18°	18°	21°	21°	21°
TANK (gal)	80	100	100	100	100	120	120
SOQUET - 10'	6	6	6	6	8	8	8
LOADING CAPACITY	3250	3500	3750	4000	4250	4500	4750
MAXIMUM HP	250	300	300	450	450	500	500
MOTOR	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin

* : dimensions and weights are not contractual