

TECHNICAL SHEETS : PROFESSIONAL HULS

V-BARGE SERIAL : 25' - 30'



COMPOSITION

- Deep "V" hull
- Marine alloy 5086 and 5052 aluminum
- Double welding, entire hull
- Self-draining and non-slip deck
- Aluminum tank below deck
- High resistance cleat
- 12 V. DC electrical system
- Hydraulic steering
- ABYC manufacturing standard
- Accessoires and modifications on request

ZONE	THICKNESS	ALUMINIUM
HULL	0.250"	#5086
SIDE	0.190"	#5086
STERN	0.250"	#5086
DECK	0.190"	#5052
STORAGE BOX	0.190"	#5052
CABIN	0.190"	#5052

DIMENSIONS AND WEIGHT *

	V-BARGE					
	25'	26'	27'	28'	29'	30'
LENGTH	25'	26'	27'	28'	29'	30'
WIDTH	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"	8' 6"
HEIGHT IN MIDDLE	40"	40"	40"	40"	40"	40"
FRANC BORD	27"	27"	27"	27"	27"	27"
DRAUGHT	13"	13"	13"	13"	13"	13"
ANGLE KEEL	12°	12°	12°	12°	12°	12°
TANK (gal)	100	100	100	100	100	100
SOQUET - 10'	6	6	6	6	6	6
LOADING CAPACITY (lbs)	2000	2200	2400	2600	2800	3000
MAXIMUM HP	300	300	350	350	400	400
MOTOR	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin	Single/Twin

* : dimensions and weights are not contractual